KPA Motion Control

KPA Motion Control is a software library for handling moving parts of machines or robots in a controlled manner. It is compliant with PLCopen specification and does not rely on specific drive model or vendor, offering a standard motion interface which can be used across various systems.

Key Features

- Linear and coordinated motion control
- · Position, velocity and torque control even for drives with limited controlling functions
- Online time-optimal trajectory generation within one control cycle
- Functional blocks according to PLCopen Part 1 and Part 4 standards
- · CiA402, SERCOS profiles supported, easy adaptation to any custom profile
- Native EtherCAT support due to own-developed EtherCAT Master
- Virtualization with CoppeliaSim robotics simulator

Versatility and Flexibility

KPA Motion Control is a tool that introduces necessary motion control capabilities into customer's control application or development environment. Due to its versatility, various application requirements can be covered:

- · Linear movements, single or multiple axis
- Synchronized, coordinated movements, with several types of axis coupling including gearing and camming

KPA Motion Control applies well to unrestricted use in multi-threaded applications and allows for interpolated unlimited axis machining, among other functions. Based on the current state of motion, it calculates an exact location for the new motion on the time-optimal trajectory. This serves to reach the desired target position with a required speed vector.

Industry Standards

KPA Motion Control is based on PLCopen specification with some extensions. It implements functional blocks as defined in PLCopen Part 1 (Linear motion) and Part 4 (Coordinated motion). For controlling drives, standard profiles CiA402, SERCOS, and CoppeliaSim are supported, which makes KPA Motion Control compatible with most of drives on the market.

Core Features

- Parallelizable for multi-core-CPUs and optimized for low end CPUs
- Simple integration of custom bus systems
- · No axes limits by design just by CPU power
- Short reaction due to close integration with EtherCAT Master
- No functional blocks limits and blending limits
- Jerk-limited, time optimal profile generation
- Dynamic and static parametrization
- · Effective feed forward control

KPA Motion Control Flyer 1




Integration

KPA Motion Control is implemented as "C" library and is not bounded to any specific CPU architecture. Moreover, its architecture includes operating system abstraction layer which enables adaptation to any operating environment. KPA Motion Control is already supporting **Microsoft Windows**, **Linux**, **INtime**, and **QNX**, other operating systems are available on the request.

Support, Assistance, and Custom Development

As a supplemental service, our team of experienced developers is ready to help you with integrating KPA Motion Control into your design environment or assist in creating motion control application.

Application Architecture



koenig-pa GmbH

Im Talesgrund 9a 91207 Lauf a.d. Pegnitz Germany https://koenig-pa.de/

Contact

email: sales@koenig-pa.de tel.: +49 9128 725 330 tel.: +49 9123 960 5796 All company processes, from a product order to technical support, are managed according to our quality management system.

Copyright © koenig-pa GmbH, Germany. All rights reserved.

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.